



LETTORE 1-WIRE DI CHIAVI ELETTRONICHE A CONTATTO

K-TA-PLUS-30 sostituisce pulsanti con gemma Ø 30 mm su pulsantiere di piano e di cabina.

Realizzato in metallo per resistere a usura e agenti atmosferici.

Il lettore integra un LED 5 V DC monocolor arancione.

DATI TECNICI

Protocollo: 1-Wire

Distanza max da controller: 15 m

Alimentazione LED: 5 V DC

Consumo LED: 1 mA

Lunghezza cavo: 200 mm

Materiale: metallo

Grado di protezione: IP 54

Temperatura operativa: da -40° a +85° C

Dimensioni foro: Ø 30 mm

Dimensioni lettore: Ø 38 x 25 mm

Peso: 30 g

CONTENUTO

1 pz K-TA-PLUS-30

1 pz MANUALE DI INSTALLAZIONE

1-WIRE READER FOR TOUCH MEMORY ELECTRONIC KEYS

K-TVS-30 replaces pushbuttons with 30 mm diameter on the floor and cabin panels.

Made of metal to withstand wear and weathering.

The reader integrates a single color orange 5 V DC LED.

TECHNICAL DATA

Protocol: 1-Wire

Maximum distance from reader: 15 m

LED supply voltage: 5 V DC

LED energy consumption: 1 mA

Cable length: 200 mm

Material: metal

Protection rating: IP 54

Operating temperature: from -40° to +85° C

Hole dimension: Ø 30 mm

Reader dimensions: Ø 38 x 25 mm

Weight: 30 g

PACKING LIST

1 pc K-TA-PLUS-30

1 pc USER MANUAL