

SELETTORE 12 V DC CON CHIAVI ELETTRONICHE CONTACTLESS RFID 13,56 MHZ

Kit selettore con chiavi elettroniche di prossimità per l'attivazione di pulsantiere di piano e di cabina.

Il selettore ha capacità di memoria per 1.364 chiavi.

La registrazione delle chiavi si effettua manualmente con la master key.

L'attivazione della pulsantiera è possibile solo avvicinando al selettore una chiave registrata.

Il kit opera da temporizzatore, impostabile da 1 a 255 secondi, o da interruttore.

Su richiesta, il kit è fornito con adattatore per foro pulsante di 30÷35 mm.

12 V DC SELECTOR WITH CONTACTLESS 13,56 MHZ RFID ELECTRONIC KEYS

Selector kit with proximity electronic keys for the activation of floor and cabin panels.

The selector has memory capacity for 1,364 keys.

Key registration is done manually with the master key or alternatively from a PC with KITPC software and hardware.

The activation of the panel is possible only by showing a registered key to the selector.

The kit operates as a timer, adjustable from 1 to 255 seconds, or as a switch.

On request, the kit is supplied with 30÷35 mm pushbutton hole adapter.



DATI TECNICI

Alimentazione: 12 V DC

Consumo: 80 mA

Memoria chiavi elettroniche: 1.364

Frequenza RFID: 13,56 MHz

Distanza di lettura RFID: 20/40 mm

Distanza max controller/lettore: 15 m

Modalità: pulsante/interruttore/temporizzatore

Timer output temporizzatore: da 1 a 255 sec

Programmazione: manuale

Grado di protezione lettore: IP 66

Temperatura operativa: da -40° a +50° C

Dimensioni foro lettore: Ø 20 mm - SU RICHIESTA Ø 30 mm

Peso: 150 g

TECHNICAL DATA

Supply voltage: 12 V DC

Stand-by energy consumption: 80 mA

Electronic keys memory: 1,364

RFID frequency: 13,56 MHz

RFID reading distance: 20/40 mm

Maximum distance controller/reader: 15 m

Mode: pushbutton/switch/timer

Timer output: from 1 to 255 sec

Programmation: manual

Reader protection rating: IP 66

Operating temperature: from -40° to +50° C

Reader hole dimensions: Ø 20 mm - ON REQUEST Ø 30 mm

Weight: 150 g

CONTENUTO

1 pz Z-5R

1 pz K-RF-MF

1 pz T-07-MF

1 pz CONTENITORE Z-5R

1 pz RELE'

1 pz REGOLATORE DI TENSIONE

1 pz MANUALE DI INSTALLAZIONE

PACKING LIST

1 pc Z-5R

1 pc K-RF-MF

1 pc T-07-MF

1 pc Z-5R CASE

1 pc RELAY

1 pc VOLTAGE REGULATOR

1 pc USER MANUAL

