



## 🇮🇹 LETTORE WIEGAND 26, 34 DI CODICI PIN E CHIAVI ELETTRONICHE CONTACTLESS RFID 125 KHZ

K-CODE-EM è un lettore da parete a due fori di fissaggio Ø 4 mm con interasse 90 mm.

In metallo e IP 68 resiste a usura, atti vandalici e agenti atmosferici. Il lettore integra un LED 5 V DC bicolore rosso e verde.

### DATI TECNICI

**Alimentazione:** 12 V DC

**Consumo:** 30 mA

**Frequenza RFID:** 125 KHz

**Distanza di lettura RFID:** 30/60 mm

**Protocollo:** Wiegand 26, 34

**Distanza max da controller:** 100 m

**Lunghezza cavo:** 200 mm

**Materiale:** metallo e ABS

**Grado di protezione:** IP 68

**Temperatura operativa:** da -45° a +60° C

**Interasse fori:** 90 mm

**Dimensioni lettore:** 120 x 58 x 22 mm

**Peso:** 500 g

## 🇬🇧 WIEGAND 26, 34 READER FOR PIN CODES AND CONTACTLESS 125 KHZ RFID ELECTRONIC KEYS

K-CODE-EM is a wall reader with two fixing holes Ø 4 mm and interaxle spacing of 90 mm.

Made of metal and IP 68, resistant to wear, vandalism and atmospheric agents.

The reader integrates a two color green and red 5 V DC LED.

### TECHNICAL DATA

**Supply voltage:** 12 V DC

**Stand-by energy consumption:** 30 mA

**RFID frequency:** 125 KHz

**RFID reading distance:** 30/60 mm

**Protocol:** Wiegand 26, 34

**Maximum distance from controller:** 100 m

**Cable length:** 200 mm

**Material:** metal and ABS

**Protection rating:** IP 68

**Operating temperature:** from -45° to +60° C

**Interaxle spacing:** 90 mm

**Reader dimensions:** 120 x 58 x 22 mm

**Weight:** 500 g

### CONTENUTO

1 pz K-CODE-EM

1 pz ADESIVO DIMA DI FORATURA

2 pz TASSELLO Ø 5 MM X 30 MM

1 pz CHIAVE TORX T10

1 pz MANUALE DI INSTALLAZIONE

### PACKING LIST

1 pc K-CODE-EM

1 pc ADHESIVE DRILLING JIG

2 pcs Ø 5 MM X 30 MM RAWLPLUGS

1 pc T10 TORX WRENCH

1 pc USER MANUAL